



Elephant Skin Wall and Wallpaper Protection

- for heavily stressed walls indoors
- water-based, cleanable protective coating



Application rate	Ca. 80-100 ml/m ² . Determine the exact coverage by applying a test coat to the object
Areas of use	<ul style="list-style-type: none">■ Particularly suitable for heavily used surfaces and surfaces that require intensive cleaning■ For wallpaper, dispersion paint coats, plastering and similar undercoats in indoor spaces
Property profile	<ul style="list-style-type: none">■ Wet abrasion resistance class I acc. to DIN EN 13 300
Directions	Drying: Surface dry after approx. 2 hours, can be painted over after approx. 12 hours The surfaces to be painted must be clean, dry, free of dust and grease, solid and load-bearing The minimum working temperature for the material and minimum ambient temperature are +8°C
Notes	Please secure the container against falls and spills during transport.
Tools / Cleaning	Clean the tools immediately after use with warm water The paint can be applied using a paint roller, paintbrush or a paint spraying device
Storage / Shelf life	Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains < 5 g/l VOC.
Precautionary statements / Hazard statements	1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one Contains. May produce an allergic reaction.,
Precautionary statements / Hazard statements	