



Stair & Parquet Flooring Varnish

- for walked-on internal wood surfaces
- abrasion and scratch-resistant sealing lacquer



Areas of use

- For wooden flooring, parquet, wooden stairs, as well as indoor furniture and doors

Directions

The wood must be well sanded (100-120 grit), clean, dry and free from grease
Permissible wood moisture: 8-12 %
For a durable seal suitable for everyday use, we recommend three coats of varnish
Do not pour directly onto the substrate as this may cause marks
Do not apply more than 2 coats per day
Do not use under 15°C (material and surface temperature)
Completely able to withstand load after 7 days (at 20°C, 65 % humidity), dust-dry after approx. 1 hour, touch-dry after approx. 2 hours, workable after approx. 4 hours

Tools / Cleaning

Acrylic brush, roller for water-based varnish (short-pile mohair or flock roller)

Storage / Shelf life

Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

VOC content as per the "Decopaint" Directive (2004/42/EC)

EU limit value for the product (Cat. A/i): max. 140 g/l (2010). This product contains < 90 g/l VOC.

Precautionary statements / Hazard statements

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1). May produce an allergic reaction.

Precautionary statements / Hazard statements