



Anti-Slip Floor Coating

- high-quality sealing of concrete, screed & cement
- for covered terraces & balconies
- for cellars, cellar staircases, storage & utility rooms



Areas of use

- For painting cellars, stairways, storage and utility rooms and other areas which are often exposed to the impact of water

Property profile

- High-grade protective coating for sealing and coating concrete/screed substrates and cement fibre boards
- Excellent light-fastness
- Weather-resistant in accordance with German construction contract procedures (VOB) part C DIN 18 363

Preparation

- **Substrate requirements**
The substrate must be clean, dry, free of grease and capable of supporting a load
- **Substrate preparation**
Smooth concrete surfaces must be roughened before applying the coating.

Directions

Old coatings must be checked for compatibility.
Stir well before use!
Dust-dry after approx. 2 hours and ready for overcoating after approx. 12 hours. Low temperatures and high humidity can delay drying
Do not use in temperatures under +8°C
Successive coats on concrete and cement, indoors and outdoors: a) Prepare the substrate accordingly; only coat concrete and cement surfaces once they have set completely (approx. 4 weeks); remove any cement slurry; b) Apply 1 coat, diluted approx. 30% with water; c) Apply 2 undiluted coats
Successive coats on top of old coats, or renovation coat: a) Check that the previous coats are compatible b) Prepare the substrate accordingly, remove any imperfections c) Apply 1-2 coats with no dilution

Tips on use

When using outdoors, make sure that surface water can run off and does not remain on the surface of the coating in puddles
Do not coat continuous surfaces with two different batches

Notes

Not suitable for garage floors!
Please secure the container against falls and spills during transport.
Colour indications are non-binding. Differences in colour may occur depending on the substrate and the printing technology used. The dried original colour will be different from the wet colour in the container. For more information, you can obtain the relevant Technical Data Sheet from www.baufix-online.com

Tools / Cleaning

Clean tools immediately after use with water and soap
Varnish brush or lambskin paint roller

Storage / Shelf life

Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Biocidal Products Regulation

Contains a biocidal product (in-can preservative) with the biocidal agents CMIT/MIT (3:1) for protecting the container content from deterioration by microbial organisms (germs, yeast, etc.). Please note the processing guidelines carefully!

Precautionary statements / Hazard statements

Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements / Hazard statements

