



Facade Paint

- for plaster, masonry, concrete, etc.
- breathable, weather-resistant protective paint



Application rate	Ca. 1 l/3 m ² . Determine the exact coverage by applying a test coat to the object
Areas of use	<ul style="list-style-type: none">■ For universal use as a preliminary coat on mineral substrates (such as masonry, concrete, render)■ Can also be used as a top-up coat on solid plastic dispersion coatings and synthetic resin plasters
Property profile	<ul style="list-style-type: none">■ Wet abrasion resistance class 3 according to DIN EN 13 300 and hiding power class 3 according to DIN EN 13 300 at 5 m² per litre
Directions	<p>The substrate must be clean, dry, free of grease and capable of supporting a load Use primer to strengthen sanding and absorbent substrates Apply the paint slowly in a crosswise motion to achieve a uniform covering Undiluted finishing coat Do not take up too much paint on the roller Do not use at an air or object temperature of below +5 °C Drying (in normal conditions, depending on the characteristics of the substrate): Surface dry after approx. 2 hours, can be painted over after approx. 6 hours</p>
Notes	<p>The standard safety measures must be observed even when using low-pollutant paints and varnishes Please secure the container against falls and spills during transport.</p>
Tools / Cleaning	<p>Clean the tools immediately after use with warm water Brush, paint roller, airless spraying equipment</p>
Storage / Shelf life	<p>Store in the sealed original container in a cool, dry, and frost-free place. Can be used for at least 1 year after the date of purchase Keep containers tightly closed and store upright to prevent spillages</p>
Disposal	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Safety advice	<p>Keep out of the reach of children. Use an A2/P2 combi-filter when spraying. Use a P2 dust filter when grinding or sanding. Ensure the area is thoroughly ventilated during application and drying. Do not eat, drink or smoke while using the paint. In the event of contact with the eyes or skin, rinse out thoroughly and immediately with water. Do not allow it to enter the ground, the sewage system or any bodies of water. Clean tools with soapy water immediately after use. Only send fully emptied containers for recycling. Take any leftover liquid material to the collection point for waste paint.</p>
VOC content as per the "Decopaint" Directive (2004/42/EC)	EU limit value for the product (Cat. A/c): max. 40 g/l (2010). This product contains < 1 g/l VOC
Precautionary statements / Hazard statements	1,2-benzisothiazol-3(2H)-one 2-methyl-2H-isothiazol-3-one Contains. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.,
Precautionary statements / Hazard statements	